

T5 FHE Luxline Plus

21W/T5/840 FHE
0002764



PRODUCT OVERVIEW

IPC Code	0002764
Product name	21W/T5/840 FHE
Technology	Fluorescent
Watt (Rated) (W)	21
Lamp shape	Tubular shape
Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUERL002
ETIM Class	EC000108
E-number FI	4944214
E-number SE	8356512
E-number Norway	3800903
Luminous flux (lm)	1900
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	92
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	85
Wattage (W)	21.00
Product Voltage (V)	126
Dimmable	Yes
Average life (Nominal) (h)	24000
Product EAN number	5410288027647

DATA TABLE

General data

IPC Code	0002764
Product name	21W/T5/840 FHE
Technology	Fluorescent
Watt (Rated) (W)	21
Lamp shape	Tubular shape

T5 FHE Luxline Plus

21W/T5/840 FHE
0002764

Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUERL002
ETIM Class	EC000108
E-number FI	4944214
E-number SE	8356512
E-number Norway	3800903

Optical data

Luminous flux (lm)	1900
Luminous flux (Rated) (lm)	1900
Luminous flux (Nominal) at 35°C (lm)	2100
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	92
Rated lamp efficacy 100h 50Hz at optimum temp. (lm/W)	100
Rated lamp efficacy 100h HF at 25°C (lm/W)	92.00
Ambient temperature for maximum luminous flux (°C)	35
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	85
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	0.97
Rated lumen maint. factor (%) at 4000 h 50Hz	0.95
Rated lumen maint. factor (%) at 6000 h 50Hz	0.93
Rated lumen maint. factor (%) at 8000 h 50Hz	0.92
Rated lumen maint. factor (%) at 12000 h 50Hz	0.91
Rated lumen maint. factor (%) at 16000 h 50Hz	0.90
Rated lumen maint. factor (%) at 20000 h 50Hz	0.88

Electrical data

Wattage (W)	21.00
Watt (Rated) - High frequency (W)	20.70
Current (A)	0.170
Product Voltage (V)	126
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Drive current (mA)	170

T5 FHE Luxline Plus

21W/T5/840 FHE
0002764

Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	23

Lifetime data

Average life (Nominal) (h)	24000
Average life (Rated) (h)	24000
Rated survival factor (%) at 2000 h 50Hz	0.99
Rated survival factor (%) at 4000 h 50Hz	0.98
Rated survival factor (%) at 6000 h 50Hz	0.96
Rated survival factor (%) at 8000 h 50Hz	0.94
Rated survival factor (%) at 12000 h 50Hz	0.93
Rated survival factor (%) at 16000 h 50Hz	0.90
Rated survival factor (%) at 20000 h 50Hz	0.84

Physical data

Nominal Product Length (mm)	850.0
Nominal Product Diameter (mm)	16
Max. Length base to base (mm) - A	849.0
Length base to pin Min-Max (mm) - B	853.7-856.1
Max. Lamp Length (mm) - C/L	863.2
Max. Lamp Diameter (mm) - D	17.0
Weight (kg)	0.064

Packaging


Single packaging type	Carton
Product EAN number	5410288027647
Packaging single length / height (cm)	86.2
Packaging single width (cm)	1.9
Packaging single depth (cm)	1.9
DUN14 (outer)	15410288027644
Units per outer package	25
Packaging outer length / height (cm)	87.6
Packaging outer width (cm)	10.5
Packaging outer depth (cm)	10.5

Safety data

Lamp mercury content (mg)	2.30
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Suitable for household illumination	Yes


PHOTOMETRY

T5 FHE Luxline Plus
21W/T5/840 FHE
0002764



TECHNICAL DRAWINGS



 **ENERG** Y IJA
IE IA
енергия · ενεργεια

SYLVANIA 0002764

A⁺⁺
A⁺ **A⁺**
A
B
C
D
E

23 kWh/1000h