

## Mini-Lynx Fast-Start

ML FAST-START 840 E27 11W SLV

0035111



### Range Features

- 



### PRODUCT OVERVIEW

Lamp finish	frosted
Lamp shape	Stick
Colour temperature (K)	4000
CRI (Ra)	80
Dimmable	No
EAN code	5410288351117
Energy class	A
Equivalent watt (W)	50
Cap/Base	E27
Type	Mini-Lynx Fast Start T3 4U Stick
Watt (Nominal) (W)	11
Light colour	840 Cool White
Ordering number	0035111
Efficacy (Rated) (lm/w)	54.5
Average life (Rated) (h)	10000
Luminous flux (Rated) (lm)	600
Technology	Compact Fluorescent
Voltage (V)	220-240

### DATA TABLE

## Mini-Lynx Fast-Start

ML FAST-START 840 E27 11W SLV

**0035111**

### General data

<b>Average life (Nominal) (h)</b>	10000
<b>Control gear required</b>	No
<b>Lamp finish</b>	frosted
<b>Lamp shape</b>	Stick
<b>Dimmable</b>	No
<b>Dry applications use only</b>	Yes
<b>EAN code</b>	5410288351117
<b>Energy class</b>	A
<b>Energy saving lamp</b>	Yes
<b>General application</b>	Hospitality; Residential & Consumer;
<b>IEC Reference</b>	IEC 60968
<b>IEC Reference 2</b>	IEC 60969
<b>IEC Reference 3</b>	IEC 55015
<b>ILCOS code</b>	FBTH-11/40/1b-E27-48/102
<b>Intended purpose</b>	General lighting
<b>Cap/Base</b>	E27
<b>Lamp mercury content (mg)</b>	<2.5
<b>Type</b>	Mini-Lynx Fast Start T3 4U Stick
<b>No. of switching cycles before premature failure (min)</b>	30000
<b>Optimal operating condition (°C)</b>	25° C, cap-up, Stated lumen output may vary if operated in non-standard position
<b>Ordering number</b>	0035111
<b>Product name</b>	ML FAST-START 840 E27 11W SLV
<b>Average life (Rated) (h)</b>	10000
<b>Special purpose lamp</b>	No
<b>Starting time (max) (s)</b>	< 1.0 Sec
<b>Technology</b>	Compact Fluorescent
<b>Transformer required</b>	No
<b>Sales pack quantity</b>	10
<b>Warm-up time to 60% of full light (max) (s)</b>	< 40 s
<b>E-number SE</b>	8357540
<b>E-number FI</b>	4940280

### Optical data

<b>Chromaticity coordinate X</b>	0.38
<b>Chromaticity coordinate Y</b>	0.38
<b>Colour temperature (K)</b>	4000
<b>CRI (Ra)</b>	80
<b>Light colour</b>	840 Cool White
<b>Lumen maintenance at end of nominal life (%)</b>	= 75.0 %

## Mini-Lynx Fast-Start

ML FAST-START 840 E27 11W SLV

**0035111**

<b>Luminous flux (Nominal) (lm)</b>	600
<b>Rated lumen maint. factor at 6000 h</b>	= 80.0 %
<b>Luminous flux (Rated) (lm)</b>	600

### Electrical data


<b>Current (A)</b>	0.085
<b>Equivalent watt (W)</b>	50
<b>kWh per 1000 hours burning time</b>	11
<b>Lamp power factor</b>	> 0.55
<b>Watt (Nominal) (W)</b>	11
<b>Efficacy (Rated) (lm/w)</b>	54.5
<b>Watt (Rated) (W)</b>	11
<b>Voltage (V)</b>	220-240

### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	48
<b>Lamp Length (mm) - C/L</b>	102
<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.06
<b>Outer package dimensions (L x W x H) (cm)</b>	25.00 x 11.00 x 13.00
<b>Single package dimensions (L x W x H) (cm)</b>	11.00 x 5.00 x 5.00

## TECHNICAL DRAWINGS

E27



## Mini-Lynx Fast-Start

ML FAST-START 840 E27 11W SLV

0035111

