

Mini-Lynx Fast-Start

ML FAST-START 827 E14 8W SLV

0035134



Range Features

-



PRODUCT OVERVIEW

Lamp finish	frosted
Lamp shape	Stick
Colour temperature (K)	2700
CRI (Ra)	80
Dimmable	No
EAN code	5410288351346
Energy class	A
Equivalent watt (W)	42
Cap/Base	E14
Type	Mini-Lynx Fast Start T3 3U Stick
Watt (Nominal) (W)	8
Light colour	827 Homelight
Ordering number	0035134
Efficacy (Rated) (lm/w)	56.25
Average life (Rated) (h)	10000
Luminous flux (Rated) (lm)	450
Technology	Compact Fluorescent
Voltage (V)	230-240

DATA TABLE

General data

Average life (Nominal) (h)	10000
----------------------------	-------

Mini-Lynx Fast-Start

ML FAST-START 827 E14 8W SLV

0035134

Control gear required	No
Lamp finish	frosted
Lamp shape	Stick
Dimmable	No
Dry applications use only	Yes
EAN code	5410288351346
Energy class	A
Energy saving lamp	Yes
General application	Hospitality; Residential & Consumer;
IEC Reference	IEC 60968
IEC Reference 2	IEC 60969
IEC Reference 3	IEC 55015
ILCOS code	FBTH-08/27/1b-E14-44/112
Intended purpose	General lighting
Cap/Base	E14
Lamp mercury content (mg)	<2.5
Type	Mini-Lynx Fast Start T3 3U Stick
No. of switching cycles before premature failure (min)	30000
Optimal operating condition (°C)	25° C, cap-up, Stated lumen output may vary if operated in non-standard position
Ordering number	0035134
Product name	ML FAST-START 827 E14 8W SLV
Average life (Rated) (h)	10000
Special purpose lamp	No
Starting time (max) (s)	< 1.50 Sec
Technology	Compact Fluorescent
Transformer required	No
Sales pack quantity	10
Warm-up time to 60% of full light (max) (s)	< 40 s
E-number SE	8357532
E-number FI	4940292

Optical data

Chromaticity coordinate X	0.463
Chromaticity coordinate Y	0.42
Colour temperature (K)	2700
CRI (Ra)	80
Light colour	827 Homelight
Lumen maintenance at end of nominal life (%)	= 75.0 %
Luminous flux (Nominal) (lm)	450
Rated lumen maint. factor at 6000 h	= 80.0 %

Mini-Lynx Fast-Start

ML FAST-START 827 E14 8W SLV

0035134

Luminous flux (Rated) (lm)	450
----------------------------	-----


Electrical data

Current (A)	0.07
Equivalent watt (W)	42
kWh per 1000 hours burning time	8
Lamp power factor	> 0.55
Watt (Nominal) (W)	8
Efficacy (Rated) (lm/w)	56.25
Watt (Rated) (W)	8
Voltage (V)	230-240

Physical data

Max. Lamp Diameter (mm) - D	44
Lamp Length (mm) - C/L	112
Single packaging type	Box/Sleeve
Weight (kg)	0.06
Inner package net weight (kg)	0.56
Inner package dimensions (L x W x H) (cm)	24.00 x 15.00 x 10.40
Outer package dimensions (L x W x H) (cm)	25.00 x 16.50 x 54.50
Single package dimensions (L x W x H) (cm)	12.00 x 4.50 x 4.50

TECHNICAL DRAWINGS



Mini-Lynx Fast-Start

ML FAST-START 827 E14 8W SLV

0035134

