



| | |
|------------------------------------|---|
| Ref. | 106D |
| Colección / Collection | Technical Indoor. Project |
| Descripción / Description | Empotrable Estanco / Recessed Water-tight |
| Material | Aluminio / Aluminium |
| Colores / Colours | 05 Inox 90-Blanco Téc. / Tec. White |
| Material Óptica / Difusor Material | Tempered Glass |
| IP ext. | 65 |
| IP int. | 20 |
| Driver Externo / External Driver | NO INCLUDED |
| Input Voltage | Max. 50W |
| Portalámpara / Lampholder | No |
| Garantía / Warranty | 5 Years |
| Diametro Exterior / Ext. Diameter | 82 mm |
| Altura / Height | 30 mm |
| Corte de techo / Ceiling Cut | 65 mm |
| Peso / Weight Kg | |
| Pcs/Ctn | 1/50 |

OTRAS OPCIONES PARA LED / OTHER OPTIONS FOR LED

Consultar pedido mínimo, precio y plazo / Please consult MOQ, price and delivery time

| | |
|--|---|
| Lámpara / Bulb LED COB (Directo a red / Direct Network GU-10) 7W | 1LHG-101 3000K 450Lm No Dim 1LHG-102 4000K 476Lm No Dim 1LHG-103 3000K 486Lm No Dim 1LHG-104 6000K 685Lm No Dim 1LHG-113 3000K 486Lm Dimmable 1LHG-114 3000K 512Lm Dimmable 1LHG-503 3000K 600Lm No Dim 1LHG-504 4000K 600Lm No Dim 1LHG-506 6000K 700Lm No Dim |
| Lámpara / Bulb LED COB (con / with Driver) 10W | 1LHX-123 3000K 936Lm No Dim 1LHX-133 3000K 936Lm Trailing 1LHX-147 3000K 936Lm 1-10V/ Push/Dali |
| Portalámpara / Lampholder | 1PHG (GU-10 100-240V Clase II) 1PHB (GU-10/GZ-10 100-240V) 1DH1 (Safety conector fast) 1DH3 (GU-10 Distanciador 100-240V Clase II) |
| JISO Smart Control | Consult |

