



Ref.	703D
Colección / Collection	Technical Indoor. Project
Descripción / Description	Empotrable Basculante Orientable / Recessed Swivel and Ajustable Spotlight
Material	Aluminio Natural / Natural Aluminium
Colores / Colours	01 Negro / Noir 05 Inox / Inox 90 Blanco Técnico / Technical White
IP Ext	20
IP Int	20
Driver Externo / External Driver	NO INCLUDED
Input Voltage	Max. 50W
Portalámpara / Lampholder	No
Garantía / Warranty	5 Years
Diametro Exterior / Ext. Diameter	95 mm
Altura / Height	30 mm
Corte de techo / Ceiling Cut	80-85 mm
Peso / Weight Kg	0,163
Pcs/Ctn	1/50

OTRAS OPCIONES PARA LED / OTHER OPTIONS FOR LED

Consultar pedido mínimo, precio y plazo / Please consult MOQ, price and delivery time

Lámpara / Bulb LED COB (Directo a red / Direct Network GU-10) 7W	1LHG-101 3000K 450Lm No Dim 1LHG-102 4000K 476Lm No Dim 1LHG-103 3000K 486Lm No Dim 1LHG-104 6000K 685Lm No Dim 1LHG-113 3000K 486Lm Dimmable 1LHG-114 3000K 512Lm Dimmable 1LHG-503 3000K 600Lm No Dim 1LHG-504 4000K 600Lm No Dim 1LHG-506 6000K 700Lm No Dim
Lámpara / Bulb LED COB (con / with Driver) 10W	1LHX-123 3000K 936Lm No Dim 1LHX-133 3000K 936Lm Trailing 1LHX-147 3000K 936Lm 1-10V/ Push/Dali
Portalámpara / Lampholder	1PHG (GU-10 100-240V Clase II) 1PHB (GU-10/GZ-10 100-240V) 1DH1 (Safety conector fast) 1DH3 (GU-10 Distanciador 100-240V Clase II)
JISO Smart Control	Consult

