



**product description:**

- designed for distribution system with voltage 400 V and with maximum current 16 A
- designed for mounting into hollow walls (eg. walls of plasterboard)
- inlet openings made of flexible material
- marked inputs for sealing cables and pipes in the flexible material (4x Ø6-10 mm, 2x Ø10-16 mm, 2x Ø20-25 mm)
- air-tightness even with inserted cable or pipe
- suitable for low energy and passive houses
- prevents airflow through the installation
- mounting screws with plastic foot are fitted with a twin self-tapping thread for quick installation
- instrument screws are tightened below the edge of the box
- extended edge situated for easy overlay installed device
- when mounting, it is not necessary to countersink the plasterboard edge
- possibility to insert screwless terminals
- when using box with the cover V 68, the IP protection is IP30

material: PVC (Pb Free)

color: yellow

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 31 g

certification: EN 60 670-1

storage: ČSN 64 0090

KPRL 64-60/LD\_NA - boxes fitted with screws for mounting into double wall and device screws - package: 84 pcs in carton

- accessories:
- cover V 68
  - screwless terminal plates TYP015, TYP016, TYP017, TYP018

- auxiliary tools:
- saw-drill VPT 64
  - universal carrier VPTU