



product description:

- designed for distribution system with voltage 400 V and with maximum current 16 A
- designed for mounting into hollow walls (eg. walls of plasterboard)
- inlet openings made of flexible material
- marked inputs for sealing pipes in the flexible material (4x 16-20 mm, 2x 20-25 mm, 12x 6-10 mm, 2x 6-9 mm)
- air-tightness even with inserted cable or pipe
- suitable for low energy and passive houses
- prevents airflow through the installation
- mounting screws with plastic foot are fitted with a twin self-tapping thread for quick installation
- instrument screws are tightened below the edge of the box
- extended edge situated for easy overlay installed device
- when mounting, it is not necessary to countersink the plasterboard edge
- mounting space in the box is divided partitions membrane
- possibility to insert screwless terminals

- material: PVC (Pb Free)
- color: yellow
- self-snuffing: yes, within 30 s
- temperature resistance: -5 - +60 °C
- flaming loop test: 850 °C
- fire class for underlying material: A1-F
- weight: 95 g
- certification: EN 60 670-1
- storage: ČSN 64 0090

KPL 64-50/3LD_NA - boxes fitted with screws for mounting into double wall and device screws - package: 30 pcs of boxes loose in carton

accessories: screwless terminal plates TYP015, TYP016, TYP017, TYP018

auxiliary tools: saw-drill VPT 64
universal carrier VPTU